

TECHNICAL DATA

valid from / gültig ab:
20.11.2012

DAMP CHAMP™

Suspension Fluid	2,5 wt	5 wt	7,5 wt	10 wt	15 wt	20 wt**
Kinematic Viscosity @ 100°C...cST	5,83	9,46	11,55	13,69	19,5	14,9
Kinematic Viscosity @ 40°C...cST	13,6	26,7	37,19	47,36	92,95	150
Viscosity Index (VI)	464	372	322	303	235	98
Specific Gravity @ 20°C	0,816	0,847	0,841	0,868	0,871	n.de
Pourpoint....°C	-37	-45	-30	-39	-39	-18
SAE Rating	0W-20	5W-30	5W-30	5W-40	5W-50	n. de
Flash Point (closed)....°C	75	120	132	140	185	250
ISO Vicosity Rating	15	22/32	32	46	100	n.de
Colour	orange	green	purple	red	yellow	yellow

** stoped to End of 2013

Available sizes: 250 ml / 1 Liter / 20 Liter

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment

Copyright r.s.p. bikecare OG, May 2021. No liability for printing and typing errors. Passing on third parties and duplication not permitted